



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO FOUR THIRDS	Olympus M.Zuiko Digital ED 30mm f3.5 Macro				36135 N85 Macro Port 45	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV 39° Converted FOV 150° Working Distance 30mm
	Olympus M.Zuiko Digital ED 60mm f2.8 Macro	36149 O60-F			36163 N85 Macro Port 65	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 2.0X Working Distance 22-70mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 2.0X Working Distance 22-70mm
						83250 M67 to Bayonet Mount Converter II	87301 EMWL Set #1	Lens FOV 20° Converted FOV 60°/100°/130°
				36620 N85 Extension Ring 20	36135 N85 Macro Port 45	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 2.0X Working Distance 22-70mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 2.0X Working Distance 22-70mm
						83250 M67 to Bayonet Mount Converter II	87301 EMWL Set #1	Lens FOV 20° Converted FOV 60°/100°/130°
						SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81302 CMC - 2	Max. Magnification 1.7X Working Distance 33-122mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2	Max. Magnification 1.7X Working Distance 33-122mm
						83250 M67 to Bayonet Mount Converter II	87301 EMWL Set #1	Lens FOV 20° Converted FOV 60°/100°/130°
	Panasonic Lumix G Macro 30mm f/2.8 Asph. Mega O.I.S.				36135 N85 Macro Port 45	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV 39° Converted FOV 150° Working Distance 30mm
	Panasonic LEICA DG MACRO-ELMARIT 45mm F2.8 ASPH. MEGA O.I.S.	36145 P45-F			36135 N85 Macro Port 45	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 1.6X Working Distance 17-73mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 1.6X Working Distance 17-73mm
						83250 M67 to Bayonet Mount Converter II	87303 EMWL Set #3	Lens FOV 20° Converted FOV 60°/100°/130°
	Laowa 24mm f/14 2X Macro Probe <i>* with Metabones T Speed Booster Ultra 0.71X Adapter on NA-GH5 housing</i>	19155 N120 DSLR Gear Set	36064 N85 to N120 34.7mm Port Adaptor	21271 Extension Ring 70 with Focus Knob	16336 N120 Port Adaptor for Laowa 24mm f/14 2X Macro Probe			

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.
Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE		
STANDARD ZOOM FOUR THIRDS	Olympus M.ZUIKO DIGITAL ED 12-40mm f/2.8 PRO	36045 O1240-Z	36052 N85 to N120 47mm Port Adaptor with Zoom Knob <i>* SN297188 onwards for NA-EM1X</i>	21120 Extension Ring 20 with Lock	36129 N85 7" Acrylic Dome Port	* 85201 WACP - 1		Lens FOV 75-45° Converted FOV 130-57° Zoom Range 14-32mm		
					* 18809 180mm Optical Glass Wide Angle Port					
		36045 + 36065 O1240-Z + O1240-F	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>	21110 Extension Ring 10 with Screws	85201 WACP - 1	18809 180mm Optical Glass Wide Angle Port			Lens FOV 75-45° Converted FOV 130-68° Zoom Range 14-26mm	
		Olympus M.ZUIKO DIGITAL ED 12-45mm f/4 PRO	36069 O1245-Z	36620 + 36620 N85 Extension Ring 20 + 20	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>	36129 N85 7" Acrylic Dome Port	36139 N85 Macro Port 35	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.7X Working Distance 24-74mm
									81302 CMC - 2	Max. Magnification 0.5X Working Distance 39-130mm
								81301 CMC - 1	Max. Magnification 0.7X Working Distance 24-74mm	
								81302 CMC - 2	Max. Magnification 0.5X Working Distance 39-130mm	
								* 18809 180mm Optical Glass Wide Angle Port		
								36064 N85 to N120 34.7mm Port Adaptor	85201 WACP - 1 <i>* this setup is not compatible with NA-EM1X</i>	Lens FOV 75-45° Converted FOV 130-58° Zoom Range 14-29mm
	36069 + 36070 O1240-Z + O1240-F	36052 N85 to N120 47mm Port Adaptor with Zoom Knob <i>* SN297188 onwards for NA-EM1X</i>	21110 Extension Ring 10 with Screws	18809 180mm Optical Glass Wide Angle Port						
Olympus M.Zuiko Digital ED 12-50mm f/3.5-6.3 EZ	36147 O1250-Z <i>* 36059 O1250-Z for NA-GH5 & NA-EM1X</i>			36137 N85 4" Acrylic Wide Angle Port	25105 + 81222 M67 Flip Diopter Holder + M67 Adaptor Ring	81301 CMC - 1	Max. Magnification 0.8X Working Distance 40-70mm			
						81302 CMC - 2	Max. Magnification 0.6X Working Distance 70-120mm			
						86201 MWL - 1	Lens FOV 39-34° Converted FOV 150-71° Working Distance 30-50mm			
						83203 WWL-C	Lens FOV 72-24° Converted FOV 110-37° Zoom Range 14-50mm			
				36161 N85 Macro Port with M77 Thread	83251 M77 to Bayonet Mount Converter II					

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.
Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance
* Secondary setup recommendation based on optical performance



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE		
STANDARD ZOOM FOUR THIRDS	Olympus M.Zuiko Digital ED 12-50mm f/3.5-6.3 EZ	36147 O1250-Z <i>*36059 O1250-Z for NA-GH5 & NA-EM1X</i>	36161 N85 Macro Port with M77 Thread	83251 + 83214 M77 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 0.8X Working Distance 14-61mm		
					81302 CMC - 2	Max. Magnification 0.7X Working Distance 24-95mm		
	Olympus M.Zuiko Digital 14-42mm f/3.5-6.3 II R	36143 O1442-Z	36137 N85 4" Acrylic Wide Angle Port	25105 + 81222 M67 Flip Diopter Holder + M67 Adaptor Ring	81301 CMC - 1	Max. Magnification 0.8X Working Distance 41-76mm		
					81302 CMC - 2	Max. Magnification 0.6X Working Distance 63-130mm		
					36136 N85 Macro Port 56	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.8X Working Distance 41-76mm
						81302 CMC - 2	Max. Magnification 0.6X Working Distance 63-130mm	
					SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 0.8X Working Distance 41-76mm	
						81302 CMC - 2	Max. Magnification 0.6X Working Distance 63-130mm	
	Olympus M.Zuiko Digital 14-42mm f/3.5-5.6 EZ	36047 O1442EZ-Z	36165 N85 Power Zoom Macro Port 29	83250 M67 to Bayonet Mount Converter II	1 83201 WWL - 1	Lens FOV 75-29° Converted FOV 130-50°		
					83202 WWL - 1B	Lens FOV 75-29° Converted FOV 130-50° <i>* zoom range for BMPCC II</i>		
	Olympus M.Zuiko Digital 14-42mm f/3.5-5.6 EZ	36143 + 36067 O1442-Z + O1442-F	36166 N85 Macro Port 56 with Focus Knob	83250 M67 to Bayonet Mount Converter II	1 83201 WWL - 1	Lens FOV 75-29° Converted FOV 130-50° <i>* zoom range for BMPCC II</i>		
					83202 WWL - 1B	Lens FOV 75-29° Converted FOV 130-50° <i>* zoom range for BMPCC II</i>		
Olympus M.Zuiko Digital 14-42mm f/3.5-5.6 EZ	36047 O1442EZ-Z	36165 N85 Power Zoom Macro Port 29	83250 M67 to Bayonet Mount Converter II	1 83201 WWL - 1	Lens FOV 75-29° Converted FOV 130-50°			
				83202 WWL - 1B	Lens FOV 75-29° Converted FOV 130-50°			
Olympus M.Zuiko Digital 14-42mm f/3.5-5.6 EZ	36047 O1442EZ-Z	36165 N85 Power Zoom Macro Port 29	83250 M67 to Bayonet Mount Converter II	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.8X Working Distance 41-76mm		
				81302 CMC - 2	Max. Magnification 0.6X Working Distance 63-130mm			
Olympus M.Zuiko Digital 14-42mm f/3.5-5.6 EZ	36047 O1442EZ-Z	36165 N85 Power Zoom Macro Port 29	83250 M67 to Bayonet Mount Converter II	SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 0.8X Working Distance 41-76mm		
				81302 CMC - 2	Max. Magnification 0.6X Working Distance 63-130mm			

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.
Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
STANDARD ZOOM FOUR THIRDS	Panasonic LUMIX G VARIO 12-32mm F3.5-5.6 ASPH. ASPH. MEGA O.I.S.	36046 P1232-Z		36620 N85 Extension Ring 20	36131 N85 3.5" Acrylic Wide Angle Port		1 83201 WWL - 1	Lens FOV 75-37° Converted FOV 130-64° Zoom Range 13-32mm	
					36165 N85 Power Zoom Macro Port 29	83250 M67 to Bayonet Mount Converter II		83202 WWL - 1B	Lens FOV 75-37° Converted FOV 130-64° Zoom Range 13-32mm
								83203 WWL-C	Lens FOV 84-37° Converted FOV 130-57°
	Panasonic LUMIX G X Vario 12-35mm F2.8 I / II ASPH. POWER O.I.S.	36148 P1235-Z		36064 N85 to N120 34.7mm Port Adaptor		36133 N85 6" Acrylic Wide Angle Port			Lens FOV 75-52° Converted FOV 130-90° Zoom Range 14-22mm
		36148 + 36042 P1235-Z + P1235-F		36052 N85 to N120 47mm Port Adaptor with Zoom Knob <i>* SN297188 onwards for NA-EM1X</i>	21120 Extension Ring 20 with Lock	36164 N85 6" Acrylic Wide Angle Port with Focus Knob			Lens FOV 75-40° Converted FOV 130-69° Zoom Range 14-30mm
						85201 WACP - 1 <i>* this setup is not compatible with NA-EM1X</i>			
						85201 WACP - 1			
						* 18809 180mm Optical Glass Wide Angle Port			
	Panasonic LEICA DG VARIO-ELMARIT 12-60mm F2.8-4.0 ASPH. POWER O.I.S.	36058 PL1260-Z		36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>	21110 Extension Ring 10 with Screws	36129 N85 7" Acrylic Dome Port			
		36058 + 36068 PL1260-Z + PL1260-F				* 18809 180mm Optical Glass Wide Angle Port			
Panasonic LUMIX G 14mm / F2.5 ASPH					36131 N85 3.5" Acrylic Wide Angle Port		1 83201 WWL - 1	Lens FOV 75° Converted FOV 130°	
					36151 N85 Pancake Port	83250 M67 to Bayonet Mount Converter II		83202 WWL - 1B	Lens FOV 75° Converted FOV 130°
Panasonic LUMIX G Vario 14-42mm F3.5-5.6 ASPH. MEGA O.I.S.	36141 P1442-Z				36137 N85 4" Acrylic Wide Angle Port	25105 + 81222 M67 Flip Diopter Holder + M67 Adaptor Ring	81301 CMC - 1	Max. Magnification 0.7X Working Distance 50-70mm	
					36121 N85 Flat Port 72	25104 + 81222 M67 Flip Diopter Holder + M67 Adaptor Ring	81302 CMC - 2	Max. Magnification 0.6X Working Distance 80-120mm	
							81301 CMC - 1	Max. Magnification 0.7X Working Distance 50-70mm	
							81302 CMC - 2	Max. Magnification 0.6X Working Distance 80-120mm	

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.
Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance
* Secondary setup recommendation based on optical performance



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
STANDARD ZOOM FOUR THIRDS	Panasonic LUMIX G Vario 14-42mm F3.5-5.6 II ASPH. MEGA O.I.S.	36057 P1442II-Z			36139 N85 Flat Port 35	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.7X Working Distance 49-72mm	
							81302 CMC - 2	Max. Magnification 0.6X Working Distance 77-122mm	
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 0.7X Working Distance 50-70mm	
		81302 CMC - 2	Max. Magnification 0.6X Working Distance 80-120mm						
		83250 M67 to Bayonet Mount Converter II	¹ 83201 WWL - 1	Lens FOV 75-29° Converted FOV 130-50°					
			83202 WWL - 1B	Lens FOV 75-29° Converted FOV 130-50°					
	Panasonic LUMIX G Vario PZ 14-42mm F3.5-5.6 ASPH. POWER O.I.S.	36146 P1442X-PZ <i>* 36061 P1442X-PZ for NA-GH5</i>				36165 N85 Power Zoom Macro Port 29	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.7X Working Distance 49-72mm
								81302 CMC - 2	Max. Magnification 0.6X Working Distance 77-122mm
							SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 0.7X Working Distance 50-70mm
	81302 CMC - 2	Max. Magnification 0.6X Working Distance 80-120mm							
	83250 M67 to Bayonet Mount Converter II	¹ 83201 WWL - 1	Lens FOV 75-29° Converted FOV 130-50°						
		83202 WWL - 1B	Lens FOV 75-29° Converted FOV 130-50°						
Panasonic LUMIX G Vario 14-45mm F3.5-5.6 ASPH. MEGA O.I.S.	36053 P1445-Z				36137 N85 4" Acrylic Wide Angle Port	25105 + 81222 M67 Flip Diopter Holder + M67 Adaptor Ring	81301 CMC - 1	Max. Magnification 0.8X Working Distance 40-75mm	
							81302 CMC - 2	Max. Magnification 0.6X Working Distance 60-130mm	
					36121 N85 Flat Port 72	25104 + 81222 M67 Flip Diopter Holder + M67 Adaptor Ring	81301 CMC - 1	Max. Magnification 0.8X Working Distance 40-75mm	
							81302 CMC - 2	Max. Magnification 0.6X Working Distance 60-130mm	
Olympus M.ZUIKO DIGITAL ED 7-14mm f/2.8 PRO	36054 + 36055 0714-Z + 0714-F	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>			18809 180mm Optical Glass Wide Angle Port				
Olympus M.ZUIKO DIGITAL ED 9-18mm f/4-5.6	36143 0918-Z	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>		21120 Extension Ring 20 with Lock	36137 N85 4" Acrylic Wide Angle Port				
		36052 N85 to N120 47mm Port Adaptor with Zoom Knob <i>* SN297188 onwards for NA-EM1X</i>		21110 Extension Ring 20 with Screws	* 18809 180mm Optical Glass Wide Angle Port				

¹ We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.
Working distance operates from the distance between the subject and the front element of the close-up lens.

^{*} Recommended port system based on best optical performance
^{*} Secondary setup recommendation based on optical performance



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT
WIDE ANGLE FOUR THIRDS	Olympus M.ZUIKO DIGITAL ED 12mm f/2.0			36620 N85 Extension Ring 20	36132 N85 4.33" Acrylic Fisheye Dome Port <i>* this setup is not compatible with NA-EM1X</i> * 36048 N85 140mm Optical Glass Fisheye Port 36131 N85 3.5" Acrylic Wide Angle Port
	Panasonic LUMIX G Vario 7-14mm F4.0 ASPH.	36044 P714-Z 36044 + 36043 P714-Z + P714-F			36133 N85 6" Acrylic Wide Angle Port 36134 N85 6" Acrylic Wide Angle Port with Focus Knob * 18809 180mm Optical Glass Wide Angle Port
	Panasonic LEICA DG VARIO-ELMARIT 8-18mm F2.8-4.0 ASPH.	36062 PL818-Z 36062 + 36063 PL818-Z + PL818-F	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>	21120 Extension Ring 20 with Lock	36129 N85 7" Acrylic Dome Port * 18809 180mm Optical Glass Wide Angle Port
FISHEYE FOUR THIRDS	Olympus M.Zuiko Digital ED 8mm f/1.8 Fisheye PRO	36056 O8-F		36617 N85 Extension Ring 17 36620 N85 Extension Ring 20	* 36048 N85 140mm Optical Glass Fisheye Port 36132 N85 4.33" Acrylic Fisheye Dome Port
	Panasonic LUMIX G FISHEYE 8mm F3.5	36041 P8-F			* 36048 N85 140mm Optical Glass Fisheye Port 36131 N85 3.5" Acrylic Wide Angle Port <i>* this setup is not compatible with NA-EM1X</i> 36132 N85 4.33" Acrylic Fisheye Dome Port
	Panasonic LUMIX G Vario PZ 14-42mm F3.5-5.6 ASPH. MEGA O.I.S. with Panasonic LUMIX G Vario DMW-GFC1 for G Series	36146 P1442X-PZ <i>* 36061 P1442X-PZ for NA-GH5</i>		36630 N85 Extension Ring 30	36132 N85 4.33" Acrylic Fisheye Dome Port
CANON EF-MOUNT	Canon EF-mount Lenses with Metabones T Speed Booster Ultra 0.71X Adapter		36064 N85 to N120 34.7mm Port Adaptor		N120 Canon EF-Mount Port System <i>* this setup is not compatible with NA-EM1X</i>

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.
Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance