



N120 PORT SYSTEM FOR CANON RF-MOUNT CAMERA SYSTEM (Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO FULL FRAME	Canon RF 85mm f/2 Macro IS STM			18701 Macro Port 60	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 1.6X Working Distance 60-85mm
					SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC		
	Canon RF 100mm f/2.8L Macro IS USM	19575 + 19576 CRF100-F + SA Control Ring		18703 Macro Port 94	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 2.3X Working Distance 29-80mm
						81202 SMC - 2	Max. Magnification 3.3X Working Distance 16-35mm
						81301 CMC - 1	Max. Magnification 2.8X Working Distance 18-85mm
						81302 CMC - 2	Max. Magnification 2.4X Working Distance 34-121mm
					SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 2.3X Working Distance 29-80mm
						81202 SMC - 2	Max. Magnification 3.3X Working Distance 16-35mm
						81301 CMC - 1	Max. Magnification 2.8X Working Distance 18-85mm
						81302 CMC - 2	Max. Magnification 2.4X Working Distance 34-121mm
				83250 M67 to Bayonet Mount Converter II	87302 EMWL Set #2	Lens FOV 24.0° Converted FOV 60°/100°/130°	
					87303 EMWL Set #3	Lens FOV 24.0° Converted FOV 60°/100°/130°	
STANDARD ZOOM FULL FRAME	Canon RF 24-70mm f/2.8L IS USM	19567 CR2470-Z	21160 Extension Ring 60 with Lock	18802 8.5" Acrylic Dome Port			
				18809 180mm Optical Glass Wide Angle Port			
				18812 230mm Optical Glass Wide Angle Port II			
			21125 + 21150 Extension Ring 25 with Lock + 50	* 18815 250mm Optical Glass Wide Angle Port II			
		19567 + 19568 CR2470-Z + CR2470-F	21250 + 21110 Extension Ring 50 with Focus Knob + 10	18802 8.5" Acrylic Dome Port			
				18809 180mm Optical Glass Wide Angle Port			
Canon RF 24-105mm f/4L IS USM	19565 CR24105-Z	21140 Extension Ring 40 with Lock	18802 8.5" Acrylic Dome Port				
			18809 180mm Optical Glass Wide Angle Port				
			* 18812 230mm Optical Glass Wide Angle Port II				

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N120 PORT SYSTEM FOR CANON RF-MOUNT CAMERA SYSTEM (Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
WIDE ANGLE FULL FRAME	Canon RF 14-35mm f/4L IS USM	19574 CR1435-Z	21155 Extension Ring 55 with Lock	18802 8.5" Acrylic Dome Port			Lens FOV 114-63° Converted FOV 140-72°	
				* 18812 230mm Optical Glass Wide Angle Port II				
				18815 250mm Optical Glass Wide Angle Port II				
				18809 180mm Optical Glass Wide Angle Port				
	Canon RF 15-35mm f/2.8L IS USM	19569 CR1535-Z	21140 Extension Ring 40 with Lock	21110 Extension Ring 10 with Screws	85204 WACP - 2		Lens FOV 110-63° Converted FOV 133-72°	
								21135 Extension Ring 35 with Lock
								21170 Extension Ring 70 with Lock
								18802 8.5" Acrylic Dome Port
								18809 180mm Optical Glass Wide Angle Port
	Canon RF 16mm f/2.8 STM						Lens FOV 110-63° Converted FOV 133-72°	
								21180 Extension Ring 80 with Lock
	Canon RF 35mm f/1.8 IS Macro STM		21271 Extension Ring 70 with Focus Knob	21235 Extension Ring 35 with Focus Knob	18812 230mm Optical Glass Wide Angle Port II		Lens FOV 110-63° Converted FOV 133-72°	
								19569 + 19570 CR1535-Z + CR1535-F
	Canon RF 35mm f/1.8 IS Macro STM						Lens FOV 110-63° Converted FOV 133-72°	
								19569 + 19571 CR1535-Z + WCR1535-F
CANON EF-MOUNT	Canon EF-mount Lenses with Canon Mount Adaptor EF-EOS R		21110 Extension Ring 10 with Screws	18706 Macro Port 12	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.9X Working Distance 20-75mm	
						81302 CMC - 2	Max. Magnification 0.8X Working Distance 24-121mm	
						81301 CMC - 1	Max. Magnification 0.9X Working Distance 20-75mm	
						81302 CMC - 2	Max. Magnification 0.8X Working Distance 24-121mm	
						83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV 42° Converted FOV 157.5°

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance